

## Scafclad 150gsm

<b>DESCRIPTION</b>	Scafclad 150gsm
<b>ROLL SIZE/ WEIGHT/ DIAMETER</b>	2m x 45m - 13.5kg - 19cm diameter 4m x 45m - 27kg - 24cm diameter (shipping length 210cm)
<b>PALLET QTY</b>	2m - 30 rolls ; 4m - 16 rolls
<b>GSM</b>	150
AS2001.2.4-1990 Method B <b>BURSTING PRESSURE</b>	Mean: 775kpa Variation: 4.3% 13032008 7-558422-MQ*
AS2001.2.10-1986 <b>TEAR RESISTANCE**</b>	Length: Mean 120N, Max 131N, Min 114N Width: Mean 87.6N, Max 106N, Min 71.9N 13032006 7-558422-MQ*
AS 2001.2.3.1-2001 <b>BREAKING FORCE &amp; ELONGATION</b> (5 Samples Tested)	Mean Length: 305N 16.4% Elongation Mean Width: 655N 14.4% Elongation 22042008 7-559201-NQ*
AS 4174, Appendix B-1994 <b>LIGHT &amp; UV</b>	56.2% Transmission 43.8% Shade Factor 50.7% UVR Block 22042008 7-559201-NQ*
<b>FLAME RETARDANT</b>	AS1530.2 Flammability Index =7
<b>COLOUR</b>	Clear sheeting, Blue reinforcing bands
<b>SOLIDITY</b>	100%



The above products have been tested in certified Laboratory conditions by approved Testing Companies.

Actual test results are only relative to the samples tested and some variation of product will occur between batches.

Different Test methods will give different results.

The above tests have been carried out to Australian Standard requirements and results are not comparable to British or any other test methods.

No warranty as to the accuracy of the test results is given by the supplier.

\*refer test reports

Version v3.0 November 2020

PRODUCED BY



Sitemax Group Pty Ltd

**NSW** 10 Edward Street  
Riverstone, NSW 2765

**QLD** 15 Dennis Little Drive  
Glanmire, QLD 4570

**BRIS** 161 Railway Parade  
Thornside, QLD 4158

**T** 07 5489 0600 | 1800 007 557

**E** sales@sitemax.com.au

[sitemax.com.au](http://sitemax.com.au)