

50% FlameX Siteclad

DESCRIPTION	50% FlameX Siteclad
ROLL SIZE/ WEIGHT/ DIAMETER	1.8 x 50m, 11kg, 22cm 3.6 x 50m, 22kg, 30cm (Shipping Length 186cm)
PALLET QTY	1.8 x 50m: 42 3.6 x 50m: 20
GSM	120
FLAME RETARDENT	AS1530.2 Flammability Index = 1 18-001348*
AS2001.2.4-1990 Method B BURSTING PRESSURE	Mean: 1400kpa Variation: 3.8% 16-000641*
AS 4174 Appendix B – 1994 LIGHT & UV	48.5% Transmission 51.5% Shade factor 55.5% UV Block 559101-MQ*
COLOUR	Black, Blue, Green, Red, Orange, White or Yellow. Custom colours upon request.
AS 2001.2.34-1990 AIR PERMABILITY	Greater than 68ml/sq.cm (outside testing range) 558653-MQ*
SOLIDITY	52.3%
MATERIAL	UV Stabilised High-density Polyethylene (HDPE)
MANUFACTURER	Manufactured in Sitemax's South Korea factory



flame 

The above products have been tested in certified Laboratory conditions by approved Testing Companies.

Actual test results are only relative to the samples tested and some variation of product will occur between batches.

Different Test methods will give different results.

The above tests have been carried out to Australian Standard requirements and results are not comparable to British or any other test methods.

No warranty as to the accuracy of the test results is given by the supplier.

*refer test reports

Version v2.0 Feb 2020

PRODUCED BY



Sitemax Group Pty Ltd

NSW 10 Edward Street
Riverstone, NSW 2765

QLD 15 Dennis Little Drive
Glanmire, QLD 4570

BRIS 161 Railway Parade
Thornside, QLD 4158

T 07 5489 0600 | 1800 007 557

E sales@sitemax.com.au

sitemax.com.au